

EDE-907-HS PRIMAX EASY LINE COMBI OVEN



Image is for illustrative purposes only © F.E.D.

EDE-907-HS Primax Convection / Steam Easy Line Oven

Gastronomy & Pastry

7 × 1/1 GN or 600×400 trays

75 mm tray spacing

Exterior: 920mmW×690D×850H; 100kg

Interior: 660mmW×420D×600H

- comes with 1 × 1/1 GN grid
- Stainless Steel
- Cooking chamber with rounded edges for easy cleaning
- Manual control of humidity (only for convection/humidification and convection/steam models)
- Cooling function (only for convection/steam models)
- Analogic, intuitive control panel
- Low-slung bottom in all models
- COMES WITH SPRAY HOSE
- Automatic reversing fan
- Double glazed door
- Internal lighting
- Snap-on seals on cooking chamber
- tray supports are adjustable with different positions (75 mm steps), easily removable for better cleaning
- Low-speed cooking (optional)
- Core probe can be fitted
- Temp. display available on order only

DESCRIPTION

EDE-907-HS Primax Convection / Steam Easy Line Oven

Gastronomy & Pastry

7 × 1/1 GN or 600×400 trays

75 mm tray spacing

Exterior: 920mmW×690D×850H; 100kg

Interior: 660mmW×420D×600H

- comes with 1 × 1/1 GN grid
- Stainless Steel
- Cooking chamber with rounded edges for easy cleaning
- Manual control of humidity (only for convection/humidification and convection/steam models)
- Cooling function (only for convection/steam models)
- Analogic, intuitive control panel
- Low-slung bottom in all models
- COMES WITH SPRAY HOSE
- Automatic reversing fan
- Double glazed door
- Internal lighting
- Snap-on seals on cooking chamber
- tray supports are adjustable with different positions (75 mm steps), easily removable for better cleaning
- Low-speed cooking (optional)
- Core probe can be fitted
- Temp. display available on order only

SPECIFICATIONS

NET WEIGHT (KG)	100
WIDTH (MM)	920
DEPTH (MM)	690
HEIGHT (MM)	850
PACKING WIDTH (MM)	840
PACKING DEPTH (MM)	950
PACKING HEIGHT (MM)	970
POWER	415V; 3~N; 9.3kW